

Product Safety Data Sheet

XEROX

Product: DocuColor 2006CP

PSDS No.: 0861
ISSUE DATE: 01/17/01
REV. DATE: 01/24/01

Section I - Product Identification

Manufacturer's Name
Xerox Corporation

Emergency No. EH&S Inquiries
(585) 422-2177 (800) 828-6571

Manufacturer's Address
Rochester, N.Y.

Product Designation
DocuColor 2006

Product Identifier:
YCA-1 for IOT
YCA-3 for Scanner

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)
100-127	10	50/60

Branch Cir. Protection
(Amps)
15

Line Cord/Plug Specification
Equipped with Appliance coupler
Detachable Cord, Two wire + Ground
NEMA 5-15P/ -20P

Power Consumption(Watts)*

Running: 451
Standby: 234

Agency Approval
UL File Number E158002
cUL File Number E158002

Section III - Supplies

	Xerox Part No.
CRU Toner, Black	6R994
CRU TONER, Cyan	6R995
CRU TONER, Magenta	6R996
CRU TONER, Yellow	6R997
Print Cartridge	13R574

Material Safety Data Sheet
Article ** (A30)
Article ** (A30)
Article ** (A30)
Article ** (A30)
Article **

Section IV - Environmental Information

Product Size (Centimeters / Inches)	Heat Emission* (BTU/HR)
D: 750 / 21.9	Running: 1533
W: 650 / 27.0	Standby: 796
H: 1160 / 16.2	

Environmental Limitations

	<u>Min</u>	<u>Max</u>
Relative Humidity (%)	15	85
Ambient Temp. (°C)	5	32

Floor Space Requirements
(Meters / Feet)
W = 2.2 / 7.3
D = 1.7 / 5.7

Weight
(K Grams / Lbs.)
IOT 86.5 / 208

* Based on a five minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2))

Section V - Emission/Exposure Information*

Light Source

FDA registered laser in a Class 1 Laser System

FDA Accession #

9820515-03

Electromagnetic Emissions

US FCC: Class A, Token Ring Class A

Canada DOC: Class A, Token Ring Class A

Audible Noise

Run 52.9 dB(A)

Standby 35.7 dB(A)

Impulse 66.7 dB(A)

TLV

85.0 dB(A)

Ozone

Concentration Based on Simulation Model:

Daily Copy Volume 136 copies/ hours

Room Size 8 m³

1/2 Air Room Change per Hour

0.01 mg/m³

0.005 ppm

TLV

0.1 ppm

Total Dust

.012 mg/m³

TLV

10 mg/m³

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time-Weighted Average) for a normal eight-hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.